

Diagnostic Fault Codes For Cummins Engines

Applies to Engine Models QSB T2, QSC T2, QSL T2, QSM11, QSX15, QSK19, QSK23, QST30, QSK45/60/78

Note: These fault codes are current at date of publication. Always refer to engine service manual for the latest information related to engine diagnostics and troubleshooting. Contact your local Cummins dealer for more information.

Fault Severity Level	Fault Severity Function	Action To Be Taken By Operator
1	Stop	Stop Engine Now – Damage Imminent
2	Warning	Warning – Engine May Continue to Run, but Must Be Repaired the Same Day
3	Maintenance	Maintenance – Repair At The Next PM
4	None- Information Only	None – No Lamp Action

FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION			•	11	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI		QSB	asc	GSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
111	S254	629	Engine Control Module – Critical internal		,,		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	.,	.,	.,	\ <u></u>			
(Red)	12	12	failure	Χ	Х	Х	Х	Х	Х	Х	Х	3	3	3
112	S020	635	Engine Timing Actuator is not responding to ECM commands						· ·	· ·		•		
(Red)	7	7	responding to ECM commands						Х	Х		2	2	2
113	S020	635	Engine Timing Actuator Circuit - shorted						· ·	· ·	· ·	•		
(Yellow)	3	3	high						Х	Х	Х	2	2	2
114	S020	635	Engine Timing Actuator Circuit - shorted								· ·			
(Yellow)	4	4	low								Х			
115	P190	190	Engine Speed/Position Sensor Circuit -											
(Red)	2	2	lost both of two signals from the magnetic pickup sensor	Х	Х	Х	Х	Х	Х	Х	Х	2	2	2
116	P156	156	Fuel Timing Pressure Sensor Circuit -		.,					.,				
(Red)	3	3	shorted high		Х	Х			Х	Х		2	2	2
117	P156	156	Fuel Timing Pressure Sensor Circuit -		.,	.,				.,				
(Red)	4	4	shorted low		Х	Х			Х	Х		2	2	2
118	P135	135	Fuel Pump Delivery Pressure Sensor		.,	.,				.,				
(Yellow)	3	3	Circuit - shorted high		Х	Х			Х	Х		3	3	3
119	P135	135	Fuel Pump Delivery Pressure Sensor		.,	.,			.,	.,		_		
(Yellow)	4	4	Circuit - shorted low		Х	Х			Х	Х		3	3	3
121	P190	190	Engine Speed/Position Sensor Circuit -											
(Yellow)	10	10	lost one of two signals from the magnetic pickup sensor		Х	Х	Х	Х	Х	Х	Х	2	2	2
122	P102	102	Intake Manifold Pressure Sensor #1	.,	.,	.,		.,		.,	.,			
(Yellow)	3	3	Circuit - shorted high	X	Х	Х	Х	Х	Х	Х	Х	2	2	2
123	P102	102	Intake Manifold Pressure Sensor #1	.,		.,		.,	.,	.,	.,			
(Yellow)	4	4	Circuit - shorted low	Χ	Х	Х	Х	Х	Х	Х	Х	2	2	2
124*		102	High Intake Manifold Pressure Left Bank								\ <u>'</u>			
(Yellow)		16									Х	3	3	3
125*		102	Low Intake Manifold Pressure Left Bank								\ <u>'</u>			
(None)		18									Х	3	3	3
126*		1129	High Intake Manifold Pressure Right								\ <u>'</u>			
(Yellow)		16	Bank								Х	3	3	3
127*		1129	Low Intake Manifold Pressure Right								.,			
(None)		18	Bank								Х	3	3	3
128*		1129	Right Bank Intake Manifold Pressure								V	^	•	
(None)		3	Sensor Circuit Failed High		L						Х	3	3	3

(**) HHP QSK45/60/78 Fault Severity Levels:
Level 1: Stop Engine Now
Level 2: Repair Engine Same Day
Level 4: Information Only



FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION			•	11	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI	2-2-31 11-31.1	QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
129*		1129	Right Bank Intake Manifold Pressure										_	_
(None)		4	Sensor Circuit Failed Low								Х	3	3	3
131	P091	091	Accelerator Pedal Position Sensor	· ·	\ \ \	. ·	· ·	· ·	· ·	· ·	· ·	•	_	
(Red)	3	3	Circuit - shorted high	X	Х	Х	Х	Х	Х	Х	Х	2	2	2
132	P091	091	Accelerator Pedal Position Sensor Circuit - shorted low	V	V	· ·	· ·	· ·	· ·	· ·	V	•	_	•
(Red)	4	4	Circuit - shorted low	X	Х	Х	Х	Х	Х	Х	Х	2	2	2
133	P029	974	Remote Accelerator Pedal Position		\ \ \	\ <u>'</u>	.,	.,			\ <u>'</u>			
(Red)	3	3	Sensor Circuit - shorted high	X	X	Х	Х	Х			Х			
133	P029	29	Remote Accelerator Pedal Position										_	_
(Red)	3	3	Sensor Circuit - shorted high						Х	Х		2	2	2
134	P029	974	Remote Accelerator Pedal Position											
(Red)	4	4	Sensor Circuit - shorted low	X	X	Х	Х	Х			Х			
134	P029	29	Remote Accelerator Pedal Position											
(Red)	4	4	Sensor Circuit - shorted low						Х	Х		2	2	2
135	P100	100	Engine Oil Pressure Sensor Circuit -											
(Yellow)	3	3	shorted high	X	Х	Х	Х	Х	Х	Х	Х	2	2	2
136*		1208	Pre Filter Oil Pressure Sensor Circuit											
(None)		3	Failed High								Х	3	3	3
137*		1208	Pre Filter Oil Pressure Sensor Circuit											
(None)		4	Failed Low								Х	3	3	3
141	P100	100	Engine Oil Pressure Sensor Circuit -											
(Yellow)	4	4	shorted low	Х	Х	Х	Х	Х	Х	Х	Х	2	2	2
143	P100	100	Engine Oil Pressure Low – Warning											
(Yellow)	1	18		Х	Х	Х	Х	Х			Х			
143	P100	100	Engine Oil Pressure Low – Warning											
(White)	1	1							Х	Х		1	1	1
144	P110	110	Engine Coolant Temperature Sensor											
(Yellow)	3	3	Circuit - shorted high	Х	Х	Х	Х	Х	Х	Х	Х	2	2	2
145	P110	110	Engine Coolant Temperature Sensor											
(Yellow)	4	4	Circuit - shorted low	X	Х	Х	Х	Х	Х	Х	Х	2	2	2
146	P110	110	Engine Coolant Temperature High –											
(Yellow)	0	16	Warning	X	Х	Х								
147	P091	091	Accelerator Pedal Position Sensor											
(Red)	8	8	Circuit - low frequency	Х	Х	Х	Х	Х	Χ	Х	Х	2	2	2
148	P091	091	Accelerator Pedal Position Sensor											
(Red)	8	8	Circuit - high frequency	X	Х	Х	Х	Х	Х	Х	Х	2	2	2
(Reu)	0	O	<u> </u>											

^(*) Denotes Cense Fault codes

Find	FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				11	15	19	23	10	QSK45	QSK60	QSK78
151	(LAMP)	FMI	FMI	DEGORIF HOR	QSB	asc	QSL	QSM	QSX1	QSK′	QSK	QST3			
Red 0	· · ·			Engine Coolant Temperature High –		 							140	IIIDCI	,
151				Critical	Х	Х	Х	Х	Х			Х			
(White)		_		Engine Coolant Temperature High –											
153				Critical						Х	Х		1	1	1
(Yellow) 3 3 3 3 3 3 3 3 3		_		Intake Manifold Temperature Sensor #1											
154				Circuit - shorted high	Х	Х	Х	Х	Х	Х	Х	Х	2	2	2
Circuit - shorted low	, ,			Intake Manifold Temperature Sensor #1											
155					Х	Х	Х	Х	Х	Х	Х	Х	2	2	2
Critical X				Intake Manifold Temperature #1 High -											
155					Х	Х	Х	Х	Х			Х			
(White) 0 Critical X X 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				Intake Manifold Temperature #1 High –											
156° (Yellow)										Х	Х		1	1	1
Yellow Sensor Circuit Failed High 2 2 2 2 2 2 2 2 2	-	0		Loft Rank Poar Intako Manifold Tomp											
157*													2	2	2
Sensor Circuit Failed Low 2 2 2 2 2 2 2 2 2 2 2	, ,			Left Dank Deer Inteke Manifeld Team											
1131	157*		1131										2	2	2
Comparison Com	(Yellow)		4												
(White) 0 Right Bank Front Intake Manifold Temperature Sensor Circuit Failed High 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	158*		1131										1	1	1
Temperature Sensor Circuit Failed High	(White)		0										·		
Yellow 3	159*		1132										2	2	2
Temperature Sensor Circuit Failed Low 2 2 2 2 2 2 2 2 2	(Yellow)		3												
Yellow 4	161*		1132										2	2	2
Right Bank Front 1 1 1 1 1 1 1 1 1	(Yellow)		4	remperature Sensor Circuit Failed Low									_	_	_
Characteristics Characteri	162*		1132												_
Temperature Sensor Circuit Failed High	(White)		0	RIGHT BAHK FIOHE									1	1	'
164*	163*		1133												
Temperature Sensor Circuit Failed Low	(Yellow)		3	Temperature Sensor Circuit Falled High									2	2	2
(Yellow) 4 High Intake Manifold Temperature - Right Bank Rear 1133 High Intake Manifold Temperature - Right Bank Rear 1 1 1 1 1 1 166 \$024 733 Rack Position Sensor #1 Circuit - shorted high X X X 172 \$023 638 Rack Actuator Position #1 Circuit - grounded circuit X X X 173 \$023 638 Rack Actuator - mechanically stuck open X X	164*		1133												
Right Bank Rear 1 1 1 1 1 1 1 1	(Yellow)		4	Temperature Sensor Circuit Failed Low									2	2	2
(White) 0 S024 733 Rack Position Sensor #1 Circuit - shorted high X X X 172 S023 638 Rack Actuator Position #1 Circuit - grounded circuit X X 173 S023 638 Rack Actuator - mechanically stuck open X	165*		1133	High Intake Manifold Temperature -											
166 S024 733 Rack Position Sensor #1 Circuit - shorted high X 172 S023 638 Rack Actuator Position #1 Circuit - grounded circuit X 173 S023 638 Rack Actuator - mechanically stuck open X				Right Bank Rear									1	1	1
(Yellow) 3 3 Shorted high X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X X		S024	733												\Box
172 S023 638 Rack Actuator Position #1 Circuit - grounded circuit X (Red) 6 6 X 173 S023 638 Rack Actuator - mechanically stuck open X				shorted high								Х			
(Red) 6 6 grounded circuit X X 173 S023 638 Rack Actuator - mechanically stuck open X X						1									
173 S023 638 Rack Actuator - mechanically stuck open				grounded circuit								Х			
				Rack Actuator - mechanically stuck open											
	(Yellow)	7	7									Х			



FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				11	15	19	23	20	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI	DEGGKII TION	QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
184	S233	609	Engine Control Module Identification											
(Yellow)	2	2	Input State Error	Х	Х	Х					Х			
185	S231	639	Engine Control Module Network											
(Yellow)	2	2	Communication Error								Х			
187	S232	620	Sensor Supply Voltage #2 Circuit -											
(Yellow)	4	4	shorted low				Х	Х						
211	S216	1484	Additional OEM/Vehicle Diagnostic											
(None)	11	31	Codes have been logged. Check other ECM's for DTC's.				Х	Х						
211*		613	OEM Component Failure											
(None)		14									Х	3	3	3
212	P175	175	Engine Oil Temperature Sensor Circuit -											
(Yellow)	3	3	shorted high				Х	Х			Х			
212*		175	Engine Oil Temperature Sensor Circuit -											
(Yellow)		3	shorted high									2	2	2
213	P175	175	Engine Oil Temperature Sensor Circuit -											
(Yellow)	4	4	shorted low				Х	Х			Х			
213*	4	175	Engine Oil Temperature Sensor Circuit -											
			shorted low									2	2	2
(Yellow) 214	P175	175	Engine Oil Temperature High - Critical											
							Х	Х						
(Red)	0	0	Engine Oil Temperature High – Critical											
214*		175	Engine on reimperature riigir ontical									1	1	1
(White)	D47	0	Low Oil Level in the Centinel makeup oil											
219	P17	1380	tank				Х	Х						
Maint.	1	17	Low Oil Level in the Centinel makeup oil											
219	P17	1380	tank						Х	Х		2	2	2
(White)	1	1	Ambient Air Pressure Sensor Circuit –											
221	P108	108	shorted high		Х	Х	Х	Х	Х	Х	Х	2	2	2
(Yellow)	3	3	Ambient Air Pressure Concer Circuit											
222	P108	108	Ambient Air Pressure Sensor Circuit – shorted low		х	Х	Х	Х	Х	Х	х	2	2	2
(Yellow)	4	4	Engine Oil Burn Value Colore id Circuit											
223	S085	1265	Engine Oil Burn Valve Solenoid Circuit – shorted low				х	х	Х	Х		2	2	2
(Yellow)	4	4	5 . 015		_									
225	S086	1266	Engine Oil Replacement Valve Solenoid Circuit - shorted low						Х	Х		2	2	2
(Yellow)	4	4										_		
227	S232	620	Sensor Supply Voltage #2 Circuit - shorted high				Х	Х						
(Yellow)	3	3	3											

^(*) Denotes Cense Fault codes

FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				11	15	19	23	00	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI	DEGOKII TION	QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
231	P109	109	Engine Coolant Pressure Sensor Circuit									140		
(Yellow)	3	3	- shorted high						Х	Х	Х	2	2	2
232	P109	109	Engine Coolant Pressure Sensor Circuit											
(Yellow)	4	4	- shorted low						Х	Х	Х	2	2	2
233	P109	109	Engine Coolant Pressure Low – Warning											
(Yellow)	1	18									Х			
233	P109	109	Engine Coolant Pressure Low – Warning											
(White)	1	1							Х	Х		1	1	1
234	P190	190	Engine Speed High – Critical											
(Red)	0	0	3 1 1 3 1 1 1 1	X	Х	Х	Х	Х	Х	Х	Х	3	3	3
235	P111	111	Engine Coolant Level Low - Critical											
				Х	Х	Х	Х	Х			Х			
(Red)	1 P111	111	Engine Coolant Level Low – Critical											
235			Zinginio deciani zevel zew dinada						Х	Х		1	1	1
(White)	1	1	External Speed Input (Multiple Unit											
237	S030	644	Sychronization) - data incorrect				Х		Х	Х		2	2	2
(Yellow)	2	2	Vahiala Chand Capper Circuit data											
241	P084	084	Vehicle Speed Sensor Circuit - data incorrect	Х	Х	Х	Х	Х						
(Yellow)	2	2	Valsiala On and One and Oissuit											
242	P084	084	Vehicle Speed Sensor Circuit - tampering has been detected	Х	X	Х	Х	Х						
(Yellow)	10	10												
243	P121	513	Engine Brake Driver #1 Circuit - shorted low	Х	X	х								
(Yellow)	4	4	· ·											
245	S033	647	Fan Clutch Circuit - shorted low	Х	X	X	x	Х						
(Yellow)	4	4						^						
252	P098	098	Engine Oil Level #1 Sensor Circuit - data incorrect									2	2	2
(Yellow)	2	2												
253	P098	098	Engine Oil Level #1 Low – Critical									1	1	1
(White)	1	1										-	'	
254	S017	632	Fuel Shutoff Valve Circuit - shorted low				Х	~			~			
(Red)	4	4					^	Х			Х			
254	S017	632	Fuel Shutoff Valve Circuit - shorted low						.,	.,		_	_	
(None)	4	4							Х	Х		2	2	2
255	S017	632	Fuel Shutoff Valve Circuit - shorted high				,,							
(Yellow)	3	3					Х	Х						
259	S017	632	Fuel Shutoff Valve - stuck open						,,	Ţ.,				
(Red)	7	7						Х	Х	Х	Х	2	2	2



FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION			0	1	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI		QSB	QSC	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		IP Lev	
261	P174	174	Fuel Temperature High – Warning											
(Yellow)	0	16		Х										
261	P174	174	Fuel Temperature High – Warning											
(White)	0	0							Х	Х		1	1	1
263	P174	174	Fuel Temperature Sensor Circuit -											
(Yellow)	3	3	shorted high		X	Х			Х	X		2	2	2
264	P174	174	Fuel Temperature Sensor Circuit - data											
(Yellow)	11	11	out-of-range	Х										
265	P174	174	Fuel Temperature Sensor Circuit -											
(Yellow)	4	4	shorted low		Х	Х			Х	X		2	2	2
268	P094	94	Fuel Pressure Sensor Circuit - data											
(Yellow)	2	2	incorrect		Х	Х								
271	S126	1347	High Fuel Pressure Solenoid Valve #1											1
(Yellow)	4	4	Circuit - shorted low		Х	Х								
272	S126	1347	High Fuel Pressure Solenoid Valve #1											
(Yellow)	3	3	Circuit - shorted high		Х	Х								
273	S127	1348	High Fuel Pressure Solenoid Valve #2											
(Yellow)	4	4	Circuit - shorted low		Х	Х								
274	S127	1348	High Fuel Pressure Solenoid Valve #2											
(Yellow)	3	3	Circuit - shorted high		Х	Х								
275	S126	1347	Fuel Pumping Element #1 (Front) -											
(Yellow)	7	7	mechanically stuck		Х	Х								
276	S018	633	Fuel Injection Control Valve Circuit -											
(Yellow)	3	3	shorted high		Х	Х								
277	S018	633	Fuel Injection Control Valve -											
(Yellow)	7	7	mechanically stuck		Х	Х								
278	P073	1075	Fuel Priming Pump Control Circuit -											
(Yellow)	11	11	shorted high/low	Х	Х	Х								
279	S018	633	Fuel Injection Control Valve Circuit -											
(Yellow)		4	shorted low		Х	Х								
	4		High Fuel Pressure Solenoid Valve #1 -											
281 (Vallow)	S126	1347	mechanically stuck		Х	х								
(Yellow)	7	7	High Fuel Pressure Solenoid Valve #2 -											
282 (Valley)	S127	1348	mechanically stuck		Х	Х]
(Yellow)	7	7	Engine Speed/Position Sensor #1		-									
283	S221	1043	(Crankshaft) Supply Voltage Circuit -	Х	Х	х								!
(Yellow)	3	3	shorted high											

^(*) Denotes Cense Fault codes

FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				11	5	6	33	0:	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI	DESCRIPTION	QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
284	S221	1043	Engine Speed/Position Sensor #1											
(Yellow)	4	4	(Crankshaft) Supply Voltage Circuit - shorted low	Х	X	Х		Х						
285	S231	639	SAE J1939 Multiplexing PGN Timeout		١.,									
(Yellow)	9	9	Error	Х	Х	Х	Х	Х						
286	S231	639	SAE J1939 Multiplexing Configuration	.,		.,								
(Yellow)	13	13	Error	Х	Х	Х	Х	Х						
287	P091	91	SAE J1939 Multiplexing Accelerator		.,	.,	.,	.,						
(Red)	2	19	Pedal Sensor System Error	Х	Х	Х	Х	Х						
288	P029	974	SAE J1939 Multiplexing Remote Throttle		\ ,	.,	.,							
(Red)	2	19	Data Error	Х	X	Х	Х	Х						
292	P223	1083	Auxiliary Temperature Sensor Input # 1						.,					
(White)	14	14	Engine Protection - Critical						Х	Х		3	3	3
293	S441	441	Auxiliary Temperature Sensor Input # 1											
(Yellow)	3	3	Circuit – shorted high											
293	P223	1083	Auxiliary Temperature Sensor Input # 1						.,					
(Yellow)	3	3	Circuit – shorted high						Х	Х		3	3	3
293	S154	1083	Auxiliary Temperature Sensor Input # 1											
(Yellow)	3	3	Circuit – shorted high				Х	Х						
294	S441	441	Auxiliary Temperature Sensor Input # 1											
(Yellow)	4	4	Circuit – shorted low											
294	P223	1083	Auxiliary Temperature Sensor Input # 1						.,	.,				
(Yellow)	4	4	Circuit – shorted low						Х	Х		3	3	3
294	S154	1083	Auxiliary Temperature Sensor Input # 1											
(Yellow)	4	4	Circuit – shorted low				Х	Х						
295	P108	108	Ambient Air Pressure Sensor Circuit -											
(Yellow)	2	2	data incorrect				Х	Х						
296	P223	1387	Auxiliary Pressure Sensor Input # 2	V	,,	,,								
(Red)	14	14	Engine Protection - Critical	Х	Х	Х								
296	P223	1084	Auxiliary Pressure Sensor Input # 2						V			^	_	_
(White)	14	14	Engine Protection - Critical						Х	Х		3	3	3
297	P223	1387	Auxiliary Pressure Sensor Input # 2	V										
(Yellow)	3	3	Circuit – shorted high	Х	X	Х								
297	P223	1084	Auxiliary Pressure Sensor Input # 2				.,	.,		.,		_	_	_
(Yellow)	3	3	Circuit – shorted high				Х	Х	Х	Х		3	3	3
298	P223	1387	Auxiliary Pressure Sensor Input # 2		.,	,,								
(Yellow)	4	4	Circuit – shorted low	Х	X	Х								



FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION			a	11	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI		QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
298	P223	1084	Auxiliary Pressure Sensor Input # 2											
(Yellow)	4	4	Circuit – shorted low				Х	Х	Х	Х		3	3	3
299	S117	1384	Engine Shutdown Commanded by											_
(None)	14	31	J1939						Х	Х		3	3	3
299	S117	1384	Engine Shutdown Commanded by											
(Yellow)	11	31	J1939				Х	Х						
311	S001	651	Injector Solenoid Valve Cylinder #1											
(Yellow)	6	6	Circuit – grounded circuit				Х	Х						
312	S005	655	Injector Solenoid Valve Cylinder #5											
(Yellow)	6	6	Circuit – grounded circuit				Х	Х						
313	S003	653	Injector Solenoid Valve Cylinder #3											
(Yellow)	6	6	Circuit – grounded circuit				Х	Х						
314	S006	656	Injector Solenoid Valve Cylinder #6											
(Yellow)	6	6	Circuit - grounded circuit				Х	Х						
315	S002	652	Injector Solenoid Valve Cylinder #2											
(Yellow)	6	6	Circuit – grounded circuit				Х	Х						
316	S078	931	Fuel Supply Pump Actuator Circuit -											
(Yellow)	3	3	shorted high						Х	Х		3	3	3
318	S078	931	Fuel Supply Pump Actuator –											
(Yellow)	7	7	mechanically stuck						Х	Х		2	2	2
319	P251	251	Real Time Clock - Power Interrupt											
Maint.	2	2	·	Х	Х	Х	Х	Х						
321	S004	654	Injector Solenoid Valve Cylinder #4											
	6	6	Circuit - grounded circuit				Х							
(Yellow)	S001	651	Injector Solenoid Valve Cylinder #1											
	5		Circuit - open circuit				Х							
(Yellow)		5	Injector Solenoid Valve Cylinder #5											
323	S005	655	Circuit – open circuit				Х							
(Yellow)	5	5	Injector Solenoid Valve Cylinder #3											
324	S003	653	Circuit – open circuit				Х							
(Yellow)	5	5	Injector Solenoid Valve Cylinder #6											
325	S006	656	Circuit – open circuit				Х							
(Yellow)	5	5	Fuel Pumping Element #2 (Rear) -											-
328	S152	1348	mechanically stuck		Х	х								
(Yellow)	7	7	Fuel System Looke 72 27727											
329	S233	1077	Fuel System Leakage error		X	Х								
(Yellow)	14	14												

FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION			6	11	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI		QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
331	S002	652	Injector Solenoid Valve Cylinder #2											
(Yellow)	5	5	Circuit – open circuit				Х							
332	S004	654	Injector Solenoid Valve Cylinder #4 Circuit – open circuit				V							
(Yellow)	5	5	Circuit – open circuit				Х							
341	S253	630	Engine Control Module – data lost				V	· ·						
(Yellow)	2	2					Х	Х						
342	S253	630	Engine Control Module – out of								.,			
(Red)	13	13	calibration								Х			
343	S254	629	Engine Control Module - Warning				\ <u>'</u>	.,	.,	.,	.,			
(Yellow)	12	12	internal hardware failure				Х	Х	Х	Х	Х	4	4	4
346	S253	630	Engine Control Module - Warning				.,	.,	.,	.,	.,			
(Yellow)	12	12	Software error				Х	Х	Х	Х	Х	4	4	4
349	P191	191	Transmission Output Shaft (Tailshaft)	.,	.,	.,	.,	.,						
(Yellow)	0	16	Speed High – Warning	X	X	Х	Х	Х						
349	P191	191	Transmission Output Shaft (Tailshaft)							.,		_		
(Yellow)	0	0	Speed High – Warning						Х	Х		2	2	2
352	S232	1079	Sensor Supply Voltage #1 Circuit -		,,	.,	\ <u>'</u>	.,						
(Yellow)	4	4	shorted low	X	X	Х	Х	Х						
361	S251	1076	Fuel Pump Control Module, Fuel Control											
(Red)	3	3	Valve Circuit - shorted high	Х										
362	S251	1076	Fuel Pump Control Module, Fuel Control	V										
(Yellow)	4	4	Valve Circuit - shorted low	Х										
363	S251	1076	Fuel Pump Control Module, Fuel Control											
(Yellow)	7	7	Valve - mechanically stuck	Х										
364	S233	1077	Fuel Pump Control Module, CAN											
(Yellow)	9	9	Communication Error - abnormal update rate	Х										
365	S233	1077	Fuel Pump Control Module, Supply											
(Yellow)	4	4	Voltage Circuit - shorted low	Х										
366	S233	1077	Fuel Pump Control Module, Supply											
(Yellow)	2	2	Voltage Circuit - data incorrect	Х										
367	P190	1078	Fuel Pump Control Module, Increment											
(Yellow)	11	11	Angle Time Sensor Error	Х										
368	S254	1078	Fuel Pump Control Module, Timing Error											
(Yellow)	8	8	3 = 1111	Х										

(**) HHP QSK45/60/78 Fault Severity Levels:
Level 1: Stop Engine Now
Level 2: Repair Enqine Same Day
Level 4: Information Only



FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				11	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI	DEGGAM HON	QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
369	P190	1078	Fuel Pump Control Module, Engine											
(Yellow)	2	2	Synchronization Error	Χ										
372	S233	1077	Fuel Pump Control Module, Idle											
(Yellow)	11	11	Validation Error	Χ										
373	S233	1077	Fuel Pump Control Module, Fuel Shutoff	V										
(Red)	3	3	Error	X										
374	S233	1077	Fuel Pump Control Module, Self-Test	V										
(Yellow)	12	12	Error	Χ										
375	S254	629	Fuel Pump Control Module, Electronic											
(Yellow)	2	2	Calibration Code Error	Χ										
376	S233	1077	Fuel Pump Control Module, Fueling or											
(Yellow)	13	13	Engine Speed Mismatch	Χ										
377	S233	1077	Fuel Pump Control Module, Stuck Relay											
(Yellow)	7	7	Error	Χ										
378	S018	633	Fueling Actuator #1 Circuit - open circuit					.,						
(Yellow)	5	5						Х						
379	S018	633	Fueling Actuator #1 Circuit - grounded					· ·						
(Yellow)	6	6	circuit					Х						
381	S237	626	Intake Air Heater (Relay Enable) #1 Circuit - data incorrect	Х	· ·	\ \ \								
(Yellow)	11	11	Circuit - data incorrect	^	X	Х								
382	S237	626	Intake Air Heater (Relay Enable) #2 Circuit - data incorrect	V		· ·								
(Yellow)	11	11	Circuit - data incorrect	Х	X	Х								
384	S237	626	Start Assist Device Control Circuit Error						· ·	· ·		٠	•	
(Yellow)	11	11	(Ether Injection)						Х	Х		3	3	3
385	S232	620	OEM Sensor Supply Voltage Circuit -		· ·	\ \ \								
(Yellow)	3	3	shorted high	X	X	Х								
386	S232	1079	Sensor Supply Voltage #1 Circuit - shorted high	V										
(Yellow)	3	3	Shorted high	Χ	X	Х	Х	Х						
387	S221	1043	Accelerator Pedal Position Sensor	V		v	V	·						
(Yellow)	3	3	Supply Voltage Circuit - shorted high	Х	Х	Х	Х	Х						
389	S033	647	Fan Clutch Circuit Error	V										
(Yellow)	11	11		Х	Х	Х								
391	S017	632	Fuel Shutoff Valve Supply Voltage error											
(Yellow)	11	11		Χ										
394	S020	635	Timing Actuator #1 Circuit - open circuit					,,						
(Yellow)	5	5						Х						

FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION			6	11	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI		QSB	asc	GSL9	QSM11	QSX15	QSK19	QSK23	QST30		IP Lev	
395	S020	635	Timing Actuator #1 Circuit - grounded					.,						
(Yellow)	6	6	circuit					Х						ı
396	S083	1244	Fueling Actuator #2 Circuit - open circuit					.,						
(Yellow)	5	5						Х						ı
397	S083	1244	Fueling Actuator #2 Circuit - grounded											
(Yellow)	6	6	circuit					Х						ı
398	S084	1245	Timing Actuator #2 Circuit - open circuit											
(Yellow)	5	5						Х						ı
399	S084	1245	Timing Actuator #2 Circuit - grounded											
(Yellow)	6	6	circuit					Х						ı
414*	S250	608	Data Communication error over the											
(Yellow)	9	9	J1587 data link Circuit								Х			ı
415	P100	100	Engine Oil Pressure Low – Critical		.,						.,			
(Red)	1	1		Χ	X	Х	Х	Х			Х			ı
415	P100	100	Engine Oil Pressure Low – Critical											
Level1	1	1							Х	Х		1	1	1
418	P097	097	Water in Fuel Indicator High –											
WIF / Maint.	0	15	Maintenance	Х	Х	Х	Х	Х			Х			
419		1319	Intake Manifold Boost Pressure											
(Yellow)		2	Imbalance								Х			
422	P111	111	Engine Coolant Level Sensor Circuit - data incorrect	V	V	· ·	V	· ·	V	· ·	V	•	•	
(Yellow)	2	2	data incorrect	Х	Х	Х	Х	Х	Х	Х	Х	2	2	2
423	P156	156	Fuel Timing Pressure or Timing Actuator Stuck						.,	.,	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	•	•	
(Yellow)	2	2	Stuck						Х	Х	Х	2	2	2
426	S231	639	SAE J1939 datalink - cannot transmit				· ·	· ·						
(None)	2	2					Х	Х						ı
426	S231	639	SAE J1939 datalink - cannot transmit						V	· ·		•	•	
(Yellow)	2	2							Х	Х		3	3	3
426*		639	SAE J1939 datalink - cannot transmit									•	•	
(None)		2										3	3	3
427	S231	639	SAE J1939 not fast enough						V	.,				
(None)		9							Х	Х		4	4	4
428	P097	97	Water in Fuel Sensor Circuit - shorted				V	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			V			
(Yellow)	3	3	high				Х	Х			Х			

(**) HHP QSK45/60/78 Fault Severity Levels:
Level 1: Stop Engine Now
Level 2: Repair Enqine Same Day
Level 4: Information Only



FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				11	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI	2200	QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
429	P097	097	Water in Fuel Sensor Circuit - shorted											
(Yellow)	4	4	low	Х	Х	Х	Х	Х			Х			
431	S230	558	Accelerator Pedal Idle Validation Circuit											
(Yellow)	2	2	- data incorrect	Х	Х	Х	Х	Х			Х			
431	P091	91	Accelerator Pedal Idle Validation Circuit											
(Yellow)	2	2	- data incorrect						Х	Х		3	3	3
432	S230	558	Accelerator Pedal Idle Validation Circuit											
(Red)	13	13	- out of calibration	Х	X	Х	Х	Х			Х			
432	P091	91	Accelerator Pedal Idle Validation Circuit											
(Red)	13	13	- out of calibration						Х	Х		3	3	3
433	P102	102	Intake Manifold Pressure Sensor Circuit											
(Yellow)	2	2	- data incorrect	Х	Х	Х	Х	Х						
434	S251	627	Power Lost without Ignition Off											
(Yellow)	2	2		Х	Х	Х	Х	Х						
435	P100	100	Engine Oil Pressure Sensor Circuit -											
(Yellow)	2	2	data incorrect				Х	Х						
441	P168	168	Battery #1 Voltage Low - Warning											1
(Yellow)	1	18		Х	Х	Х	Х	Х			Х			
441	P168	168	Battery #1 Voltage Low - Warning											
(None)	1	1							Х	Х		3	3	3
442	P168	168	Battery #1 Voltage High - Warning											
(Yellow)	0	16		Х	Х	Х	Х	Х			Х			
442	P168	168	Battery #1 Voltage High – Warning											
(Yellow)	0	0							Х	Х		2	2	2
443	S221	1043	Accelerator Pedal Position Sensor											
(Yellow)	4	4	Supply Voltage Circuit - shorted low	Х	Х	Х	Х	Х						
444	S232	620	OEM Sensor Supply Voltage Low -											
(Yellow)	1	18	Warning	Х	Х	Х								
446*		N/A	GSP Communication Failure											
(None)		13/7									Х	4	4	4
447*		N/A	RPC Number Not Supported											
(None)		13//3									Х	4	4	4
448*		N/A	RPC Argument Mismatch											
(None)		18//3	_								Х	4	4	4
449	P094	094	Fuel Pressure High - Warning											
			J		Х	Х		Х						!
(Yellow)	0	16												<u> </u>

FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				11	15	19	23	08	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI	3 2 3 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 	QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
451	P157	157	Injector Metering Rail #1 Pressure											
(Yellow)	3	3	Sensor Circuit - shorted high		Х	Х		Х						
451	P157	157	Injector Metering Rail #1 Pressure											
(Red)	3	3	Sensor Circuit - shorted high						Х	Х		2	2	2
452	P157	157	Injector Metering Rail #1 Pressure											
(Yellow)	4	4	Sensor Circuit - shorted low		Х	Х		Х						
452	P157	157	Injector Metering Rail #1 Pressure											
(Red)	4	4	Sensor Circuit - shorted low						Х	Х		2	2	2
455	S018	633	Fuel Control Valve Circuit - shorted high											
(Red)	3	3							Х	Х		2	2	2
466	S032	1188	Turbocharger #1 Wastegate Control											
(Yellow)	4	4	Circuit - shorted low					Х						
467	S020	635	Timing Rail Actuator Circuit - data											
(Yellow)	2	2	incorrect						Х	Х		2	2	2
468	S018	633	Fuel Rail Actuator Circuit - data incorrect											
(Yellow)	2	2							Х	Х		2	2	2
471	P098	98	Engine Oil Level Low – Maintenance											
Maint.	1	1										1	1	1
472	P017	1380	Engine Oil Level #2 Low – Maintenance											
Maint.	2	2										3	3	3
473	P017	1380	Engine Oil Level #2 Low – Warning											
(Yellow)	2	2										2	2	2
479*	_	1318	Exhaust Port Temperature Bank											
(None)		9	Imbalance								Х			
482	P094	094	Fuel Pressure Low - Warning											
(Yellow)	1	18	-					Х						
483	P129	1349	Injector Metering Rail #2 Pressure											
(Yellow)	3	3	Sensor Circuit - shorted high					Х						
484	P129	1349	Injector Metering Rail #2 Pressure											
(Yellow)	4	4	Sensor Circuit - shorted low					Х						
485	P129	1349	Injector Metering Rail #2 Pressure High -		-									
(Yellow)	0	16	Warning					Х						
486	P129	1349	Injector Metering Rail #2 Pressure Low -										$\vdash \vdash$	
	1	18	Warning					Х						
(Yellow) 487		626	Start Assist Device - Canister Empty		\vdash								$\vdash\vdash$	\vdash
	S237		(Ether Injection)						Х	Х		3	3	3
(None)	1	1												



FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				7	5	61	23	02	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI	DESCRIPTION	QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
488	P105	105	Intake Manifold Temperature High –											
(Yellow)	0	16	Warningl	Х	Х	Х								
489	P191	191	Transmission Output Shaft (Tailshaft)											
(Yellow)	1	18	Speed Low – Warning	Х	Х	Х	Х	Х						
489	P191	191	Transmission Output Shaft (Aux Gov)											
(Yellow)	1	1	Speed Low – Warning						Х	Х		2	2	2
(TCIIOW)	S018	1076	Fuel Pump Calibration Trim Circuit Error											
493	13	13	·		Х	Х								
496	S221	1043	Engine Speed/Position Sensor #2											
	11		(Camshaft) Supply Voltage					Х						
(Yellow)		11	Multiple Unit Synchronization Switch											
497	S114	1377	Circuit - data incorrect	Х	Х	Х			Х	Х		2	2	2
(Yellow)	2	2	Fuel Central Valve, mechanically study											
514	S018	633	Fuel Control Valve - mechanically stuck						Х	X		2	2	2
(Red)	7	7								Х				
515	P091	091	Accelerator Pedal Frequency Position Sensor Supply Circuit - shorted high	Х	X	х								
(Yellow)	3	3												
516	P091	091	Accelerator Pedal Frequency Position Sensor Supply Circuit - shorted low	Х	×	Х								
(Yellow)	4	4	Conson Cupply Circuit Circuited low	^		^								
517	S251	1076	Fuel Metering Solenoid - bad device	V										
(Yellow)	12	12		Χ										
524	P113	113	OEM Alternate Droop Switch Validation											
(Yellow)	2	2	- data incorrect	Х	X	Х					Х			
527	P154	702	Auxiliary Input/Output #2 Circuit -											
(Yellow)	3	3	shorted high	Х	X	Х	Х	Х			Х			
527	S040	702	Auxiliary Input/Output #2 Circuit -											
(Yellow)	3	3	shorted high						Х	Х		2	2	2
528	P093	093	OEM Alternate torque validation switch -											
(Yellow)	2	2	data incorrect	X	Х	Х	Х	Х			Х			
529	S051	703	Auxiliary Input/Output #3 Circuit -		-									
(Yellow)	3	3	shorted high	X	Х	Х	Х	Х	Х	Х	Х	2	2	2
			Injector Control Valve Electronic Filter											
539	S018	633	(Transorb) Error		Х	Х								
(Yellow)	11	11	Fuel Delivery Pressure Sensor Circuit -		-									
546	P094	94	shorted high					Х						
(Yellow)	3	3	Fuel Delivery Processes O. C.											
547	P094	94	Fuel Delivery Pressure Sensor Circuit- shorted low					х						
(Yellow)	4	4												

^(*) Denotes Cense Fault codes

FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				11	5	6	13	0	QSK45	QSK60	QSK78
(LAMD)	FMI	FMI	DESCRIPTION	QSB	QSC	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
(LAMP) 551	S230	558	Accelerator Pedal Idle Validation Circuit		+	Ŭ	Ť	Ŭ				Nu	mber	()
(Yellow)	4	4	- shorted low	Х	Х	Х	Х	Х			Х			
,	P091		Accelerator Pedal Idle Validation Circuit											
551		091	- shorted low						Х	Х		2	2	2
(Red)	4	4	Injector Metering Rail #1 Pressure High -											-
553	P157	157	warning level					Х						
(Yellow)	0	16	Liste star Materia - Deil #4 December High											
553	P157	157	Injector Metering Rail #1 Pressure High - warning level						Х	Х		2	2	2
(Red)	0	0												
554	P157	157	Fuel Pressure Sensor Error						Х	Х		2	2	2
(Yellow)	2	2							^	^			_	_
555	P022	1264	Engine Blowby - Warning Level								Х			
(Yellow)	0	16									^			
555	P022	1264	Engine Blowby - Warning Level							· ·				
(White)	0	0							Х	Х		1	1	1
581	P015	1381	Fuel Supply Pump Inlet Pressure Sensor											
(Yellow)	3	3	Circuit - shorted high				Х	Х			Х			
582	P015	1381	Fuel Supply Pump Inlet Pressure Sensor											
(Yellow)	4	4	Circuit – shorted low				Х	Х			Х			
583	P015	1381	Fuel Supply Pump Inlet Pressure Low -											
(Yellow)	1	18	warning level				Х	Х			Х			
595	P103	103	Turbocharger #1 Speed High - warning											
(Yellow)	0	16	level					Х						
596	P167	167	Electrical Charging System Voltage High											
(Yellow)	0	16	- warning level				Х	Х						
597	P167	167	Electrical Charging System Voltage Low											
(Yellow)	1	18	- Warning Level				Х	Х						
598	P167	167	Electrical Charging System Voltage Low											
(Red)	1	1	- Critical Level				Х	Х						
599	S025		OEM Commanded Dual Output		1									
		640	Shutdown	Х	Х	Х								
(Red)	14	14	Engine Hot Shutdown		-									
611	S151	1383	Engine Flot Officiown	Х	Х	Х	Х	Х						
(None)	11	31	Engine Het Shutdown		-	-	-							
611	S151	1383	Engine Hot Shutdown						Х	Х	Х	3	3	3
(None)	14	31			1									
612*		99	High Lubricating Oil Filter Restriction								Х	2	2	2
(Red)		1												



FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				11	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI		QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
616*		1173	High Turbo Compressor Inlet Temp RB											
(None)		16										3	3	3
617*		1172	High Turbo Compressor Inlet Temp LB											
(None)		0									Х			
621*		1137	Low #1 LB Cylinder Power								.,			
(Yellow)		18									Х	2	2	2
622*		1138	Low #2 LB Cylinder Power											
(Yellow)		18									Х	2	2	2
623*		1139	Low #3 LB Cylinder Power											
(Yellow)		18									Х	2	2	2
624*		1140	Low #4 LB Cylinder Power											
(Yellow)		18									Х	2	2	2
625*		1141	Low #5 LB Cylinder Power									_		
(Yellow)		18									Х	2	2	2
626*		1142	Low #6 LB Cylinder Power											
(Yellow)		18									Х	2	2	2
627*		1143	Low #7 LB Cylinder Power											
(Yellow)		18											2	2
628*		1144	Low #8 LB Cylinder Power											
(Yellow)		18											2	2
		1143	Low #1 RB Cylinder Power											
631*		(45) 1145										_		
(Yellow)		(60)										2	2	2
		18												
631*		1329	Low #1 RB Cylinder Power								V			
(Yellow)		1									Х			
		1144	Low #2 RB Cylinder Power											
632*		(45) 1146										2	2	2
(Yellow)		(60)												
		18												
632*		1329	Low #2 RB Cylinder Power								Х			
(Yellow)		1									^			
		1145	Low #3 RB Cylinder Power											
633*		(45) 1147										2	2	2
(Yellow)		(60)										_	_	-
		18												

FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				11	15	61	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI	DECORIF HON	QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30	HI	HP Le	vel (**)
633*	1	1329	Low #3 RB Cylinder Power									140	IIIDCI	
(Yellow)		1									Х			
634* (Yellow)		1146 (45) 1148 (60)	Low #4 RB Cylinder Power									2	2	2
		18	Low #4 RB Cylinder Power											
634*		1329	Low #4 RB Cyllider Fower								Х			
(Yellow)		1												
635* (Yellow)		1147 (45) 1149 (60)	Low #5 RB Cylinder Power									2	2	2
635*		1329	Low #5 RB Cylinder Power											
(Yellow)		1	,								Х			
636* (Yellow)		1148 (45) 1150 (60)	Low #6 RB Cylinder Power									2	2	2
636*		1329	Low #6 RB Cylinder Power								Х			
(Yellow)		1	Low #7 DD Codindor Dower											
637*		1151	Low #7 RB Cylinder Power										2	2
(Yellow)		18												
638*		1152	Low #8 RB Cylinder Power										2	2
(Yellow)		18											_	_
641*		1137	High #1 LB Cylinder Exhaust Temperature								Х	2	2	2
(Red)		0	· ·								^			
642*		1138	High #2 LB Cylinder Exhaust Temperature								Х	•	,	•
(Red)		0	Temperature								^	2	2	2
643*		1139	High #3 LB Cylinder Exhaust								\ ,	_	_	
(Red)		0	Temperature								Х	2	2	2
644*		1140	High #4 LB Cylinder Exhaust									_		
(Red)		0	Temperature								Х	2	2	2
645*		1141	High #5 LB Cylinder Exhaust											
(Red)		0	Temperature								Х	2	2	2
646*		1142	High #6 LB Cylinder Exhaust Temperature								Х	2	2	2
(Red)		0	remperature								^	_	~	_



FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION			6	11	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI		QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
647*		1143	High #7 LB Cylinder Exhaust											
(Red)		0	Temperature										2	2
648*		1144	High #8 LB Cylinder Exhaust										_	
(Red)		0	Temperature										2	2
649	S115	1378	Change Lubricating Oil and Filter						V	_		٠	3	
(None)	0	0							Х	Х		3	3	3
651* (Red)		1143 (30,45) 1145 (60)	High #1 RB Cylinder Exhaust Temperature								Х	2	2	2
652* (Red)		1144 (30,45) 1146 (60)	High #2 RB Cylinder Exhaust Temperature								X	2	2	2
653* (Red)		1145 (30,45) 1147 (60)	High #3 RB Cylinder Exhaust Temperature								х	2	2	2
654* (Red)		1146 (30,45) 1148 (60)	High #4 RB Cylinder Exhaust Temperature								x	2	2	2
655* (Red)		1147 (30,45) 1149 (60)	High #5 RB Cylinder Exhaust Temperature								х	2	2	2
656* (Red)		1148 (30,45) 1149 (60)	High #6 RB Cylinder Exhaust Temperature								Х	2	2	2
657*		1150	High #7 RB Cylinder Exhaust										_	
(Red)		0	Temperature										2	2
658*		1151	High #8 RB Cylinder Exhaust Temperature										2	2
(Red)		0											_	2
659*			Change fuel filter								Х	1	4	1
(None)											^	4	4	4

FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				11	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI	BESSIAI TION	QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
661*		1137	High #1 LB Cylinder Power											
(Yellow)		16										2	2	2
661*		1323	High #1 LB Cylinder Power											
(Yellow)		0									Х			
662*		1138	High #2 LB Cylinder Power									_		
(Yellow)		16										2	2	2
662*		1324	High #2 LB Cylinder Power								.,			
(Yellow)		0									Х			
663*		1139	High #3 LB Cylinder Power											
(Yellow)		16										2	2	2
663*		1325	High #3 LB Cylinder Power											
(Yellow)		0									Х			
664*		1140	High #4 LB Cylinder Power											
(Yellow)		16										2	2	2
664*		1326	High #4 LB Cylinder Power											
(Yellow)		0									Х			
665*		1141	High #5 LB Cylinder Power											
(Yellow)		16										2	2	2
665*		1327	High #5 LB Cylinder Power											
(Yellow)		0									Х			
666*		1142	High #6 LB Cylinder Power											
(Yellow)		16										2	2	2
666*		1328	High #6 LB Cylinder Power								.,			
(Yellow)		0									Х			
667*		1143	High #7 LB Cylinder Power											
(Yellow)		16											2	2
668*		1144	High #8 LB Cylinder Power											
(Yellow)		16											2	2
669*			Change coolant filter										,	
(None)											Х	4	4	4
671*		1137	Cyl #1 LB Exhaust Temp Sens Failed											
(None)		4	Low								Х	4	4	4
672*		1138	Cyl #2 LB Exhaust Temp Sens Failed								.,	_		
(None)		4	Low								Х	4	4	4
673*		1139	Cyl #3 LB Exhaust Temp Sens Failed											
(None)		4	Low								Х	4	4	4



FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION			0	11	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI		QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
674*		1140	Cyl #4 LB Exhaust Temp Sens Failed											
(None)		4	Low								Х	4	4	4
675*		1141	Cyl #5 LB Exhaust Temp Sens Failed								.,			
(None)		4	Low								Х	4	4	4
676*		1142	Cyl #6 LB Exhaust Temp Sens Failed								V	_	_	
(None)		4	Low								Х	4	4	4
677*		1143	Cyl #7 LB Exhaust Temp Sens Failed Low										,	
(None)		4	Low										4	4
678*		1144	Cyl #8 LB Exhaust Temp Sens Failed										,	
(None)		4	Low										4	4
679*			Change Coolant											
(None)											Х	Х	4	4
691*		1172	LBF Turbo Comp Inlet Temp Sens								\ <u>'</u>			
(None)		3	Failed High								Х			
692*		1172	LBR Turbo Comp Inlet Temp Sens Failed Low								V			
(None)		4	Falled Low								Х			
694*		1173	RBF Turbo Comp Inlet Temp Sens									٠	٠	
(None)		3	Failed High									3	3	3
695*		1174	RBR Turbo Comp Inlet Temp Sens Failed Low									٠	٠	
(None)		4	Falled Low									3	3	3
		1143	High #1 RB Cylinder Power											
711*		(45) 1145										2	2	2
(Yellow)		(60										2		
		16												
711*		1329	High #1 RB Cylinder Power								Х			
(Yellow)		0									^			
		1144	High #2 RB Cylinder Power											
712*		(45) 1146										2	2	2
(Yellow)		(60)										_	_	-
		16	111 1 10 DD 0 11 1 D											
712*		1330	High #2 RB Cylinder Power								Х			
(Yellow)		0	11: 1 #0 PP O I: 1 P											
		1145 (45)	High #3 RB Cylinder Power											
713*		1147										2	2	2
(Yellow)		(60)												
		16												

FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION			6	111	15	19	23	30	QSK45	09XSD	QSK78
(LAMP)	FMI	FMI		QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Lev	
713*		1331	High #3 RB Cylinder Power								.,			
(Yellow)		0									Х			
714* (Yellow)		1146 (45) 1148 (60)	High #4 RB Cylinder Power									2	2	2
714*		1332	High #4 RB Cylinder Power											
(Yellow)		0									Х			
715* (Yellow)		1147 (45) 1148 (60)	High #5 RB Cylinder Power									2	2	2
		16	High #5 RB Cylinder Power											
715*		1333	High #5 RB Cyllider Fower								Х			
(Yellow)		0	High #6 RB Cylinder Power											
716* (Yellow)		1148 (45) 1149 (60) 16	Tilgit #0 IXB Gyillidei I owel									2	2	2
716*		1334	High #6 RB Cylinder Power								.,			
(Yellow)		0									Х			
717*		1150	High #7 RB Cylinder Power											
(Yellow)		0											2	2
718*		1151	High #8 RB Cylinder Power											
(Yellow)		0											2	2
719 (Yellow)	P022	1264 3	Crankcase Blowby Pressure Sensor Circuit - shorted high						х	х	х	2	2	2
721* (None)		1143 (30,45) 1145 (60)	Cyl #1 RB Exhaust Temp Sens Failed Low								X	4	4	4
722* (None)		1144 (30,45) 1146 (60)	Cyl #2 RB Exhaust Temp Sens Failed Low								х	4	4	4



FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION			6	11	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI	BESSIAII HON	QSB	asc	GSL9	QSM11	QSX15	QSK19	QSK23	QST30	HI Nu	HP Lev	/el (**)
723* (None)		1145 (30,45) 1147 (60)	Cyl #3 RB Exhaust Temp Sens Failed Low								X	4	4	4
724* (None)		1146 (30,45) 1148 (60)	Cyl #4 RB Exhaust Temp Sens Failed Low								Х	4	4	4
725* (None)		1147 (30,45) 1149 (60) 4	Cyl #5 RB Exhaust Temp Sens Failed Low								X	4	4	4
726* (None)		1148 (30,45) 1150 (60)	Cyl #6 RB Exhaust Temp Sens Failed Low								X	4	4	4
727* (None)		1151 4	Cyl #7 RB Exhaust Temp Sens Failed Low										4	4
728* (None)		1152 4	Cyl #8 RB Exhaust Temp Sens Failed Low										4	4
729 (Yellow)	P022 4	1264 4	Crankcase Blowby Pressure Sensor Circuit - shorted low						х	х	Х	2	2	2
747* (None)			Trend Data Memory Nearly Full								Х	4	4	4
748* (None)			Trend Data Memory Full								Х	3	3	3
749* (None)			Fault Log Snapshot Data Nearly Full								Х	4	4	4
753 (None)	S064 2	723 2	Engine Speed/Position #2 - Cam sync error					х	х	х		3	3	3
754* (None)			Fault Log Snapshot Data Full								Х	3	3	3
755 (Yellow)	P157 7	157 7	Injector Metering Rail #1 Pressure Malfunction					х						

FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				11	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI		QSB	QSC	QSL9	QSM11	QSX15	QSK19	QSK23	QST30		HP Le	
756*			Change Lubricating Oil Filters								.,			
(None)											Х	4	4	4
757*			Catastrophic Power Loss - ECM Data								.,			
(None)			Lost								Х	4	4	4
758	P129	1349	Injector Metering Rail #2 Pressure Malfunction					,,						
(Yellow)	7	7	Manunction					Х						
768	S009	923	Output Device Driver (VGT or	.,	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	,,								
(Yellow)	11	11	Transmission shift PWM signal)	X	X	Х								
777	P173	1180	Turbocharger #1 Turbine Inlet						.,					
(Yellow)	0	0	Temperature High - warning level						Х			2	2	2
779	S051	703	Auxiliary Equipment Sensor Input # 3	.,	1.,									
(Yellow)	11	11	(OEM Switch)	X	Х	Х								
783			Rapid Rise in Intake Manifold Temperature LBF										1	1
951	P166	166	Cylinder Power Imbalance between											
(None)	2	2	cylinders				Х	Х						
1000*			Vehicle Controller initiated fault log								.,			
(None)											Х			
2144*	0	1153 0	High #9 LB Cylinder Exhaust Temperature											2
0445*	0		High #9 RB Cylinder Exhaust											
2145*	0	1154 0	Temperature											2
0440#		1153	Exhaust Gas Temperature Sensor											
2146*	4	4	Circuit Failed Low Cyl # 9 RB											4
011=		1154	Exhaust Gas Temperature Sensor											
2147*	4	4	Circuit Failed Low Cyl # 9 LB											4
04.40*		1340	High Power – Cylinder # 9 Left Bank											•
2148*	0	16												2
04.40*		1341	High Power – Cylinder # 9 Right Bank											•
2149*		16												2
0454*		1340	Low Power – Cylinder # 9 Left Bank											_
2151*		18												2
0450*		1341	Low Power – Cylinder # 9 Right Bank											_
2152*		18												2
2154*		611	Post-Filter Oil Pressure Sensor Circuit-								\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	_	_	_
(None)		3	Shorted high								Х	3	3	3

(**) HHP QSK45/60/78 Fault Severity Levels:
Level 1: Stop Engine Now
Level 2: Repair Engine Same Day
Level 4: Information Only



FAULT CODE	SID(S) PID(P)	SPN	DESCRIPTION				7	15	19	23	30	QSK45	QSK60	QSK78
(LAMP)	FMI	FMI	DESCRIPTION	QSB	asc	QSL9	QSM11	QSX15	QSK19	QSK23	QST30	HHP Level Number (**)		
2155*		611	Post-Filter Oil Pressure Sensor Circuit-											
(None)		4	Shorted Low								Χ	3	3	3
2157*		1131	Rapid Rise in Intake Manifold											
		10	Temperature LBR										1	1
2158*		1132	Rapid Rise in Intake Manifold		+									
		10	Temperature RBF										1	1
2159*		1133	Rapid Rise in Intake Manifold											
		10	Temperature RBR										1	1
2194*	P223	1387	Auxiliary Equipment Sensor Input # 2											
(Yellow)	11	11	(OEM Pressure Sensor) Engine	Χ	Х	Х								
, ,			Protection – Warning Auxiliary Equipment Sensor Input # 3											
2195*	S051	703	(OEM Switch) Engine Protection -	Х	Х	Х								
(Red)	14	14	Critical											
2241*			Left Bank Middle High Intake Manifold Temperature - EP											2
2242*			Left Bank Middle Intake Manifold Temp											2
00.10*			Sensor Circuit Failed High Left Bank Middle Intake Manifold Temp											
2243*			Sensor Circuit Failed Low											2
2244*			Rapid Rise in Intake Manifold Temperature LBM											2
2245*			Right Bank Middle High Intake Manifold Temperature - EP											2
2246*			Right Bank Middle Intake Manifold Temp Sensor Circuit Failed High											2
2247*			Right Bank Middle Intake Manifold Temp Sensor Circuit Failed Low											2
2248*			Rapid Rise in Intake Manifold Temperature RBM											2
2251*			Front Intercooler Boost Pressure High											2
2252*			Front Intercooler Boost Pressure Low											2
2253*			Front Intercooler Boost Pressure Out of Range High											2
2254*			Front Intercooler Boost Pressure Out of Range Low											2
2255*			Rear Intercooler Boost Pressure High											2
2256*			Rear Intercooler Boost Pressure Low											2
2257*			Rear Intercooler Boost Pressure Out of Range High											2
2258*			Rear Intercooler Boost Pressure Out of Range Low											2

This page is intentionally blank.